



# EZ-WRAP PAK

## PRECUT BUTYL RUBBER JOINT WRAP with SPRAY ADHESIVE

### What It Is

**EZ-WRAP PAK** is a package of precut sections of 6" wide EZ-WRAP Plastic Joint Wrap. Each package contains sections of wrap cut perfectly for 48" (1200 mm), 60" (1500 mm), or 72" 1800 mm) manhole joints, and the necessary amount of spray adhesive primer.

EZ-WRAP is an extruded butyl adhesive tape designed to provide high strength, watertight seals on properly primed concrete surfaces and concrete structure joints of any kind. The butyl compound is soft, tacky, and bonded to a plastic backing. The tape is wound in rolls on a release liner for easy application.

### Why It's Better

- Precut sections of EZ-WRAP save time and money.
- Easy-to-use spray adhesive gives great bond.
- No cutting means less loss and waste.
- High quality butyl rubber base.
- Supplied in 6" (150 mm) width with HDPE backing.
- All-weather performance.
- Good adhesion to dry concrete, commonly specified concrete coatings, steel, glass, or painted surfaces.
- Coated release paper for easy installation.
- Long service life.

### How It Performs

**EZ-WRAP PAK BUTYL JOINT WRAP** meets or exceeds all requirements of the following Standards, Specifications and/or Test Methods:

**ASTM C 877 (Type III)** - Standard Specification for External Sealing Bands for Concrete Pipe, Manholes, and Precast Box Sections



Scan Here To View More Info On This Product On The Web!

Press-Seal believes all information is accurate as of its publication date. Information, specifications, and prices are all subject to change without notice. Press-Seal is not responsible for any inadvertent errors. Copyright 2012.



EZ WRAP-PAKS (6" (150 mm) wide Plastic)			
Manhole Size	Roll Length	No. Rolls	Part No.
<b>48" ID X 5"</b>	<b>16 ft</b>	6	276.616
1200 x 125 mm	4.9 m		
<b>60" ID X 6"</b>	<b>20 ft</b>	5	276.620
1500 x 150 mm	6.1 m		
<b>72" ID X 7"</b>	<b>24 ft</b>	4	276.624
1800 x 175 mm	7.3 m		

### **SUBMITTAL SPECIFICATION for BUTYL JOINT WRAP WITH PLASTIC BACKING**

The joints and/or joining surfaces of the structures shall be sealed with a butyl-rubber-based tape. The material shall be EZ-WRAP Plastic as supplied by PRESS-SEAL GASKET CORPORATION, Fort Wayne, Indiana, or approved equal. The butyl component of the tape shall consist of 50% (min.) butyl rubber, shall contain 2% or less volatile matter, and shall be .050" (1.3 mm) thick. The backing component shall be high-density polyethylene film. A release paper may be utilized.

The tape width shall be 6" (150 mm) wide. The tape shall be overlapped at least twice its width. The tape shall not be stretched during application. Primer and/or adhesive as recommended by the tape supplier shall be employed for adverse, critical, or other applications.

Testing of joints and compliance with construction requirements shall be conducted in strict conformance with the requirements of the sealant supplier.





# SUPER STICK SPRAY ADHESIVE

## ADHESIVE SPRAY

### What It Is

**SUPER STICK SPRAY ADHESIVE** is a fast drying, super strength adhesive for bonding rubber to concrete and other substrates. **SUPER STICK SPRAY ADHESIVE** is a great general purpose rubber cement that is packaged in a convenient 16 oz. aerosol can.

### Why It's Better

- Fast drying.
- High strength.
- Adjustable spray nozzle.
- Convenient aerosol.
- Methylene chloride free formula.



### Method of Application

- Shake well prior to use.
- Surfaces should be clean, dry and free of debris.
- Spray adhesive using a web pattern to insure coverage.
- Allow solvent to flash for 1 to 3 minutes, until tacky, and then press rubber to adhesive.



Press-Seal believes all information is accurate as of its publication date. Information, specifications, and prices are all subject to change without notice. Press-Seal is not responsible for any inadvertent errors. Copyright 2012.

