

# Kor-N-Seal<sup>®</sup> II

## 506 Series Pipe-to-Manhole Connector



- *Stormwater connectors for 15.00 - 33.63" O.D. pipe*
- *Designed with the EX Series expansion band system*
- *Meets ASTM C1478-07 Specifications for Storm Drain Resilient Connectors*
- *Cost-effective solution to watertight storm system connections*



*Patented Waveband technology creates a more effective seal by concentrating the compressive force of the expansion band. The rubber is "captured" between the band and the concrete.*

# Kor-N-Seal II

## 506 Series Pipe-to-Manhole Connector

### Using Corrugated Pipe

Adapters are required when using Corrugated Pipe. Refer to the Corrugated Pipe Adapter Data Sheet for details.

NOMINAL HOLE SIZE	MODEL NUMBER	PIPE O.D. RANGE	MINIMUM MANHOLE SIZE REQUIRED
18"	S506-18L	15.000 - 15.625	48/4
20"	S506-20	15.625 - 17.000	48/4
20"	S506-20L	17.000 - 17.625	48/4
22"	S506-22	17.625 - 19.000	48/4
22"	S506-22L	19.000 - 19.625	48/4
24"	S506-24	19.625 - 21.000	48/5
24"	S506-24L	21.000 - 21.625	48/5
26"	S506-26	21.625 - 23.000	48/5
26"	S506-26L	23.000 - 23.625	48/5
28"	S506-28	23.625 - 25.000	48/5
28"	S506-28L	25.000 - 25.625	48/5
30"	S506-30	25.625 - 27.000	48/6
30"	S506-30L	27.000 - 27.625	48/6
32"	S506-32	27.625 - 29.000	60/6
32"	S506-32L	29.000 - 29.625	60/6
34"	S506-34	29.625 - 31.000	60/6
34"	S506-34L	31.000 - 31.625	60/6
36"	S506-36	31.625 - 33.000	72/7
36"	S506-36L	33.000 - 33.625	72/7

