

# Seaboard Asphalt Products Company



PRODUCT DATA                      ASPHALT PAINT  
LN-12 QUICK DRYING ASPHALT GILSONITE PAINT

**PRODUCT DESCRIPTION:** Seaboard Gilsonite Paint is a superior quick drying asphalt paint formulated to meet Federal Specification TTC-494 Types I, II, and III.

**BASIC USES:** Seaboard Gilsonite Paint is used as a tough and weather resistant coating on all types of steel, piping, industrial equipment chassis, radiators, burial vaults, etc.

**LIMITATIONS:** DO NOT HEAT container.

**APPLICATION:** Seaboard Gilsonite Paint may be brushed or sprayed onto a clean and dry surface. This material dries in one hour and cures in approximately five hours.

**STORAGE:** Seaboard Gilsonite Paint should be kept in a warm area before usage during cold seasons, but this material can be used year round and the only protection would be from weathering on the container.

**COMPOSITION:**

Asphalt	CAS 8052-42-4
Mineral Spirits	CAS 64741-41-9
Gilsonite	CAS 12002-43-6

This information is to assist customers in determining if this product is suitable for the proposed application, and to satisfy themselves as to suitability of the contents. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from law or patent implied.

**3601 FAIRFIELD ROAD  
BALTIMORE, MARYLAND 21226  
(410) 355-0330  
(800) 536-0332  
FACSIMILE (410) 355-5864**

Email: [sales@seboardasphalt.com](mailto:sales@seboardasphalt.com)