

# Kor-N-Seal® II

## 306 Series Pipe-to-Manhole Connector



- *Allows you to fit large diameter pipe into the smallest possible manhole structures*
- *Can be used in cored or formed holes*
- *Meets the specifications of ASTM C923*
- *Easy-to-install*



*The Patented 4" wide Stainless Steel Korbond is able to overcome the curvature of smaller sized manholes and provide a watertight seal.*




# Kor-N-Seal® II 306 Series Connector



# TRELLEBORG

P/N	Suggested Pipe O.D. Range	Hole Size Range				Pipe Clamp		Minimum Manhole Size
		A	B	C	D	Qty	P/N	
S306-22	17.625 - 18.500	21.98 - 22.13	19.875	19	10.5	2	I-318	36/4
S306-22L	18.500 - 19.625			20		2	I-348	
S306-24	19.625 - 20.500	23.98 - 24.13	21.875	21	10.5	4	I-180	36/4
S306-24L	20.500 - 21.625			22		4		
S306-26	21.625 - 22.500	26.00 - 26.20	23.875	23	10.5	4	I-190	36/4
S306-26L	22.500 - 23.625			24		4	I-218	
S306-28	23.625 - 24.500	28.00 - 28.20	25.875	25	10.5	4	I-218	48/5
S306-28L	24.500 - 25.625			26		4		
S306-30	25.625 - 26.500	30.00 - 30.20	27.875	27	10.5	4	I-218	48/5
S306-30L	26.500 - 27.625			28		4	I-242	
S306-30L-32	26.500 - 27.625	32.00 - 32.20	29.875	28	10.5	4	I-242	48/5
S306-32	27.625 - 28.500	32.00 - 32.20	29.875	29	10.5	4	I-242	48/5
S306-32L	28.500 - 29.625			30		4		
S306-34	29.625 - 30.500	34.00 - 34.20	31.875	31	10.5	4	I-258	48/5
S306-34L	30.500 - 31.625			32		4		
S306-36	31.625 - 32.500	36.00 - 36.20	33.250	33	10.5	4	80667 Power Gear	60/6
S306-36L	32.500 - 33.000			34		4		
S306-36-STORM	31.625 - 32.500	36.00 - 36.20	33.875	33	10.5	4	I-282	60/6
S306-36L-STORM	32.500 - 33.625			34		4		
S306-38	33.625 - 34.500	38.00 - 38.20	35.250	35	10.5	4	80667 Power Gear	60/6
S306-38L	34.500 - 35.000			36		4		
S306-38LS-PG	34.500 - 35.625	38.00 - 38.20	35.875	36	10.5	4	80667 Power Gear	60/6
S306-38-STORM	33.625 - 34.500	38.00 - 38.20	35.875	35	10.5	4	I-282	60/6
S306-38L-STORM	34.500 - 35.625			36		4	I-306	
S306-40	35.625 - 36.500	40.00 - 40.20	37.250	37	10.5	4	80667 Power Gear	60/6
S306-40L	36.500 - 37.000			38		4		
S306-40-STORM	35.625 - 36.500	40.00 - 40.20	37.875	37	10.5	4	I-306	60/6
S306-40L-STORM	36.500 - 37.625			38		4		
S306-42	37.625 - 38.500	42.00 - 42.20	39.250	39	10.5	6	80682 Power Gear	72/7
S306-42L	38.500 - 39.000			40		6		
S306-42-STORM	37.625 - 38.500	42.00 - 42.20	39.875	39	10.5	4	I-318	72/7
S306-42L-STORM	38.500 - 39.625			40		4	I-348	
S306-44	39.625 - 40.500	44.00 - 44.20	41.250	41	10.5	8	80682 Power Gear	72/7
S306-44L	40.500 - 41.000			42		8		
S306-44LS-PG	40.500 - 41.625	44.00 - 44.20	41.875	42	10.5	8	80682 Power Gear	72/7
S306-44-STORM	39.625 - 40.500	44.00 - 44.20	41.875	41	10.5	4	I-348	72/7
S306-44L-STORM	40.500 - 41.625			42		4		
S306-46	41.625 - 42.500	46.00 - 46.20	43.250	43	10.5	6	80667 Power Gear	72/7
S306-46L	42.500 - 43.000			44		6		
S306-46-STORM	41.625 - 42.500	46.00 - 46.20	43.875	43	10.5	4	I-348	72/7
S306-46L-STORM	42.500 - 43.625			44		4		
S306-48	43.625 - 44.500	48.00 - 48.20	45.250	45	10.5	6	80667 Power Gear	72/7
S306-48L	44.500 - 45.000			46		6		
S306-48-STORM	43.625 - 44.500	48.00 - 48.20	45.875	45	10.5	6	I-242	72/7
S306-48L-STORM	44.500 - 45.625			46		6	I-258	



\*Adapters are required when using corrugated pipe. Refer to the Corrugated Pipe Adapter Data Sheet for details.

Covered under U.S. Patent No. 6,641,176



Trelleborg Pipe Seals Milford, Inc.  
 250 Elm Street, P.O. Box 301, Milford, New Hampshire 03055 U.S.A.  
 Tel: 800-626-2180 603-673-8680 Fax: 603-673-7271 www.trelleborg.com/npc