

CSD SLIPSIL PLUG CHART FOR USE WITH PVC PIPING

Service Pipe Run		Steel Pipe Sleeve to Use			SLIPSIL Part Numbers
IPS (in.)	OD (in.)	IPS (in.)	Schedule	Min. Length	
1/2	.840	2	40	120mm	53/20-22 FRR/SIL
3/4	1.050	2	40	120mm	53/26-28 FRR/SIL
1	1.315	2	40	120mm	53/33-34 FRR/SIL
1-1/4	1.66	3	40	160mm	78/42-44 FRR/SIL
1-1/2	1.90	3	40	160mm	78/48-50 FRR/SIL
2	2.375	4	40	160mm	103/60-62 FRR/SIL
2-1/2	2.875	4	40	160mm	103/72-74 FRR/SIL
3	3.50	5	40	160mm	128/88-90 FRR/SIL
3-1/2	4.00	6	40	160mm	154/100-102 FRR/SIL
4	4.50	6	40	160mm	154/114-116 FRR/SIL
5	5.583	8	40	160mm	203/141 FRR/SIL
6	6.625	8	40	160mm	203/168 FRR/SIL
Contact CSD	1-603-293-0100	E-Mail: info@csdsealingsystems.com			Rev 02/08