



Est Weights:
 Top Slab - 8,100 Lbs
 Base - 23,100 Lbs
 Total: 31,200 Lbs

General Notes:

1. Steel Reinforcement Conforms to Latest ASTM Specifications: ASTM-A615 Grade 60 Rebar
2. Concrete: $f_c = 5,000$ psi @ 28 Days Minimum
3. Flexible Sleeves Provided On All Pipe Connections
4. Butyl Rubber Joint Sealant Provided
5. Internal PVC Baffles Available Upon Request
- Inlet: Shall Penetrate at Least 9" Below the Liquid Level, But Not Deeper Than the Outlet Baffle.
- Outlet: Shall Extend Below the Surface of the Liquid Equal to 40% of the Liquid Depth (19").
6. Design Loading: AASHTO-HS20-44, ASTM C-890-06
7. Design Specified As: ASTM C-1227-08, ASTM C-913-08
8. Other Inlet/Outlet Pipe Sizes Available

"A" Liquid Levels: = 338 Gals/VF(28Gals/In)	4" PVC Inverts:
"B" Liquid Levels: = 180 Gals/VF(15Gals/In)	Inlet-57"
4": "A"= 1,380 Gallons	Outlet-54"
"B" = 720 Gallons	
6": "A"= 1,350 Gallons	6" PVC Inverts:
"B" = 705 Gallons	Inlet-56"
	Outlet-53"

Phoenix Precast Products	1300 / 700
	2 Compartment H-20 Tank

P/N: ST-1300/700H20

Concord, NH 03301