



| Height | Weight     |
|--------|------------|
| 3'-0"  | 2,775 Lbs  |
| 3'-6"  | 3,240 Lbs  |
| 4'-0"  | 3,700 Lbs  |
| 4'-6"  | 4,165 Lbs  |
| 5'-0"  | 4,625 Lbs  |
| 5'-6"  | 5,090 Lbs  |
| 6'-0"  | 5,550 Lbs  |
| 6'-6"  | 6,015 Lbs  |
| 7'-0"  | 6,475 Lbs  |
| 7'-6"  | 6,940 Lbs  |
| 8'-0"  | 7,400 Lbs  |
| 8'-6"  | 7,865 Lbs  |
| 9'-0"  | 8,325 Lbs  |
| 9'-6"  | 8,790 Lbs  |
| 10'-0" | 9,250 Lbs  |
| 10'-6" | 9,715 Lbs  |
| 11'-0" | 10,175 Lbs |
| 11'-6" | 10,640 Lbs |

**Dimensions:**  
 A.) Total Base Height \_\_\_\_\_  
 B.) Bolt Projection \_\_\_\_\_  
 C.) Depth of Conduit \_\_\_\_\_  
 D.) Reveal Above Grade \_\_\_\_\_  
 E.) Bolt Circle Diameter \_\_\_\_\_  
 F.) Ground Wire - \_\_\_\_\_  
 G.) Conduit (PVC) \_\_\_\_\_  
 H.) Anchor Bolts - Dia & Length \_\_\_\_\_

**General Notes:**  
 1. Concrete:  $f_c = 5,000$  PSI @ 28 Days Min  
 2. Reinforcing Steel: ASTM A615 Grade 60 Rebar

Phoenix  
 Precast  
 Products

**30" Square  
 Light Pole Base**