



Phoenix Precast Products

Phoenix Precast Products

General Notes:

1. Concrete: $f_c = 5,000$ psi @ 28 Days Minimum
2. Steel Reinforcement Conforms to Latest ASTM Specifications: ASTM-A615 Grade 60 Rebar
3. Flexible Sleeves Provided On All Pipe Connections
4. Butyl Rubber Joint Sealant Provided
5. Internal PVC Baffles Available Upon Request
Inlet: Shall Penetrate at Least 9" Below the Liquid Level, But Not Deeper Than the Outlet Baffle.
Outlet: Shall Extend Below the Surface of the Liquid Equal to 40% of the Liquid Depth (24").
6. Design Loading: AASHTO-HS20-44, ASTM C-890-06
7. Design Specified As: ASTM C-1227-08, ASTM C-913-08
8. Other Inlet/Outlet Pipe Sizes Available

4" PVC Inverts: Inlet - 87" Outlet - 84"
 6" PVC Inverts: Inlet - 86" Outlet - 83"

Liquid Levels: 7'-0" x 15'-0" = 787 Gals/VF

4" PVC = 5,115 Gallons
 6" PVC = 5,052 Gallons

Est. Weight:

Top:	27,200 Lbs
Bottom:	22,800 Lbs
Total:	50,000 Lbs

**Phoenix
Precast
Products**

**5,000 Gallon
H-20 Tank**

P/N: ST-5000H20