



Liquid Levels: 9' x 16' = 1,080 Gals/VF

4" PVC = 5,940 Gals Inverts: Inlet-77" Outlet-74"

6" PVC = 5,854 Gals Inverts: Inlet-76" Outlet-73"

General Notes:

1. Steel Reinforcement Conforms to Latest ASTM Specifications: ASTM-A615 Grade 60 Rebar
2. Concrete: $f_c = 5,000$ psi @ 28 Days Minimum
3. Flexible Sleeves Provided On All Pipe Connections
4. Butyl Rubber Joint Sealant Provided
5. Internal PVC Baffles Available Upon Request
- Inlet: Shall Penetrate at Least 9" Below the Liquid Level, But Not Deeper Than the Outlet Baffle.
- Outlet: Shall Extend Below the Surface of the Liquid Equal to 40% of the Liquid Depth (26").
6. Design Loading: AASHTO-HS20-44, ASTM C-890-06
7. Design Specified As: ASTM C-1227-08, ASTM C-913-08
8. Other Inlet/Outlet Pipe Sizes Available

Est Weights:

Top Slab - 20,200 Lbs
 5' Riser - 19,900 Lbs
 Base - 22,700 Lbs
 Total Weight: 62,800 Lbs

Phoenix
 Precast
 Products

6000 Gallon
 H-20 Tank

P/N: ST-6000H20

Concord, NH 03301