




Liquid Levels: 9' x 16' = 1,080 Gals/VF

4" PVC = 8,100 Gals Inverts: Inlet-101" Outlet-98"

6" PVC = 8,003 Gals Inverts: Inlet-100" Outlet-97"

General Notes:

1. Steel Reinforcement Conforms to Latest ASTM Specifications: ASTM-A615 Grade 60 Rebar
2. Concrete: $f_c = 5,000$ psi @ 28 Days Minimum
3. Flexible Sleeves Provided On All Pipe Connections
4. Butyl Rubber Joint Sealant Provided
5. Internal PVC Baffles Available Upon Request
- Inlet: Shall Penetrate at Least 9" Below the Liquid Level, But Not Deeper Than the Outlet Baffle.
- Outlet: Shall Extend Below the Surface of the Liquid Equal to 40% of the Liquid Depth (36").
6. Design Loading: AASHTO-HS20-44, ASTM C-890-06
7. Design Specified As: ASTM C-1227-08, ASTM C-913-08
8. Other Inlet/Outlet Pipe Sizes Available

Est Weights:

Top Slab:	21,300 Lbs
3'-6" Riser:	18,900 Lbs
3' Riser:	16,300 Lbs
Base:	28,100 Lbs
Total:	84,600 Lbs

Phoenix
Precast
Products

8000 Gallon
H-20 Tank

P/N: ST-8000H20

Concord, NH 03301